

Silk-Screen Adhesive SP310*

Water Based, Screen-Printable Adhesive for Temporary Tattoos

NT19ADH
(12/14)

Product Description:

Silk-Screen Adhesive SP310 was specifically formulated for temporary tattoos. A water-based emulsion, SP 310 contains less than 0.5% VOC's; only water is evaporated during processing. SP310 exhibits ideal viscosity and rheology with great leveling. This results in a smooth, professional adhesive layer that maximizes skin contact and extends tattoo life. **NOTE: This adhesive is designed for use on a printing press. It is not intended to be applied directly to the skin in its wet state.**

Application / Use:

SP310 is recommended for mesh counts of 60 through 230 tpi. Although its shear-thinning qualities allow a wide range of mesh counts to be used, typically 110 tpi mesh provides ideal adhesive thickness for temporary tattoos.

Prep:	Mix adhesive thoroughly before use
Screen:	110 tpi mesh
Stencil:	Image Mate DZ 343 photoemulsion (no hardener required)*
Printing environment:	50% or higher relative humidity
Drying:	Hot air dryer for rapid curing; racking in a dry area (< 50%
humidity) Cured:	Adhesive will be optically clear when thoroughly dry
Stencil cleaning:	Hot water for wet adhesive; dry adhesive can be removed readily using acetone.

Physical Properties:

Polymer Type:	Acrylic copolymer emulsion
Appearance:	White liquid, dries clear
Viscosity / Rheology:	~ 13,000 cps / thixotropic
Solids:	58 - 62 %
pH:	3.7 – 4.7
Wt. per gallon:	8.6 lbs.
VOC content:	< 0.5% by wt. (calculated)
Freeze/Thaw Stable:	No
Shelf life:	1 year minimum

Compliance Information:

Non-irritant as defined by 16 CFR

1500.3(C)(4); Complies with California

Proposition 65

SP310 does not contain any FDA cosmetic restricted substances

SP310 does not contain any animal products or byproducts

For more information, contact your Colorcon representative or call 1-800-724-0624
You can also visit our website at [http:// www.colorcon.com/notox](http://www.colorcon.com/notox)

©BPSI Holdings LLC, 2014

The information contained in this document is proprietary to Colorcon Inc. and may not be used or disseminated inappropriately.
All trademarks, except where noted, are property of BPSI Holdings, LLC.

The information contained herein, to the best of Colorcon Inc.'s knowledge, is true and accurate. Any recommendations or suggestions of Colorcon Inc. with regard to the products provided by Colorcon Inc. are made without warranty, either implied or expressed, because of the variations in methods, conditions and equipment which may be used in commercially processing the products, and no such warranties are made for the suitability of the products for any applications that you may have disclosed. Colorcon Inc. shall not be liable for loss of profit or for incidental, special or consequential loss or damages. The information contained in this document is not intended as legal advice, and should not be relied upon for that purpose. Any regulatory information provided is intended solely as initial general guidance. Each customer is responsible for determining the regulatory acceptability of the use of the product in their specific application.

