

No-Tox[®] GRAVURE VINYL INKS

(GRAVURE OR OFFSET GRAVURE)

NT14
(10/14)

- Printing Method:** Gravure or offset gravure.
- Suggested Uses:** Specifically designed for printing onto films such as PVC, polystyrene, polyurethane and acrylic or PVDC coated polyolefins which will come into direct contact with food or drug products or are parts of medical devices or medical packaging.
- Specific Characteristics:** A one-part air dry or heat assisted system exhibiting excellent adhesion and scuff resistance when applied to the substrates above. Offers excellent chemical and heat resistance characteristics.
- Plates, Cylinders and Offset Rollers:** Standard gravure cylinders can be used. Offset rollers or blankets must be made from silicone elastomers, synthetic rubbers or photopolymers resistant to ketone and ester solvents.
- Note:** Flexographic printing is possible if ketone resistant plates are used.
- Additives and Diluents*:** Normally supplied at higher than “press-ready” viscosities to allow for diluent and drying rate adjustments at press-side to accommodate specific running speeds or other requirements.
- Recommended Solvents:** The following solvents and blends are intended only as a guide. Other diluents and/or ratios may be better suited for your specific application. For additional assistance, contact our Technical Services Department.
- Normal: 100% Methyl Isobutyl Ketone
- Fast: 100% Methyl Ethyl Ketone
- Slow: 50% Methyl Isoamyl Ketone
50% Ethyl Lactate
- Wash up:** Any of the materials used as solvents as listed above.
- Color Availability:** Black, blue, red, yellow and white. Special matches are available upon request, subject to minimum order quantities.
- Shelf Life:** Minimum one year in unopened containers.
- FDA Acceptability*:** All components used in No-Tox inks are sanctioned by the FDA and USDA as acceptable for direct food contact. All medical device inks can be submitted to the FDA for inclusion in Colorcon No-Tox Products’ Drug Master File #17155 and are manufactured under strict cGMP guidelines in our dedicated facility.

*Note: FDA acceptability is based on the ink as supplied. Therefore, no materials should be added other than those indicated in this bulletin unless specifically recommended by Colorcon.



For more information, contact your Colorcon representative or call 1-800-724-0624
You can also visit our website at <http://www.colorcon.com/notox>

©BPSI Holdings LLC, 2014

The information contained in this document is proprietary to Colorcon Inc. and may not be used or disseminated inappropriately.
All trademarks, except where noted, are property of BPSI Holdings, LLC.

The information contained herein, to the best of Colorcon Inc.'s knowledge, is true and accurate. Any recommendations or suggestions of Colorcon Inc. with regard to the products provided by Colorcon Inc. are made without warranty, either implied or expressed, because of the variations in methods, conditions and equipment which may be used in commercially processing the products, and no such warranties are made for the suitability of the products for any applications that you may have disclosed. Colorcon Inc. shall not be liable for loss of profit or for incidental, special or consequential loss or damages. The information contained in this document is not intended as legal advice, and should not be relied upon for that purpose. Any regulatory information provided is intended solely as initial general guidance. Each customer is responsible for determining the regulatory acceptability of the use of the product in their specific application.