



nutrafinish[®]
Dietary Supplement Coating

Nutrafinish[®] Products Cleaning Guidelines

Nutrafinish[®], dietary supplement coating, is a one-step product combining polymer, plasticizer, pigment, and other additives as required, in a dry powder form. It provides excellent film forming capabilities including sharp logo definition, high tensile strength and good adhesion properties.

The cleaning instructions listed below are general recommendations for most Nutrafinish products. Individual cleaning products and equipment specifications should be considered, and conditions altered as required.

- For best results, Nutrafinish should be cleaned off equipment shortly after the end of the coating run.
- If cleaned properly, Nutrafinish residue is easily removed using a site approved cleaning agent. The cleaning agent does not need to be alkaline or acidic in nature.
- Prepare a solution of the cleaning agent in room temperature or cold water. Do not use hot water as it can cause gelation of certain polymers used in coating formulations.
- Spray this solution onto the surfaces to be cleaned.
- Wait 3-5 minutes for the solution to settle on the sprayed surfaces.
- Rinse the sprayed surfaces with purified water until clean.

COATING PANS

- Coating pans can be cleaned with the same cleaning agent solution.
- Fill the reservoir with the cleaning agent solution and allow the pan to rotate through the solution for 30 minutes.

SPRAY EQUIPMENT

- Guns and hoses should be disassembled and cleaned.
- When cleaning spray guns, it is important to make sure the passages are free of residual coating material that can block the orifice and restrict flow.
- A thin soft brush or swab can be passed through the tip of the nozzle to ensure all the coating material is removed.
- Avoid using hard substances, because these can damage the gun parts. All equipment should be rinsed with purified water after cleaning.

The information contained herein, to the best of Colorcon, Inc.'s knowledge is true and accurate. Any recommendations or suggestions of Colorcon, Inc. with regard to the products provided by Colorcon, Inc. are made without warranty, either implied or expressed, because of the variations in methods, conditions and equipment which may be used in commercially processing the products, and no such warranties are made for the suitability of the products for any applications that you may have disclosed. Colorcon, Inc. shall not be liable for loss of profit or for incidental, special or consequential loss or damages.

Colorcon, Inc. makes no warranty, either expressed or implied, that the use of the products provided by Colorcon, Inc., will not infringe any trademark, trade name, copyright, patent or other rights held by any third person or entity when used in the customer's application.

For more information, contact your Colorcon representative or call:

North America
+1-215-699-7733

Europe/Middle East/Africa
+44 (0)-1322-293000

Latin America
+54-11-5556-7700

India
+91-832-6727373

China
+86-21-61982300

You can also visit our website at **www.colorcon.com**



© BPSI Holdings LLC, 2020. The information contained in this document is proprietary to Colorcon, Inc. and may not be used or disseminated inappropriately.

All trademarks, except where noted, are property of BPSI Holdings LLC.

pi_nutrafinish_cleaning_v1_12_2020