

GUIDELINES FOR USING DIRECT FOOD CONTACT SOLVENT BASED INKS BY FLEXOGRAPHY

NS28
(9/14)

- Ink Preparation:***
- If cold, allow ink to come to room temperature.
 - If ink is in kits or drums, thoroughly mix before using.
 - If ink is in one-gallon containers, shake well to homogenize.

- Press Preparation:***
- Thoroughly clean ink pans, doctor blades (chambers) and anilox rolls with the appropriate solvents for the conventional inks previously run.
 - Use only new, clean lint-free rags. Chemically treated or scented rags should also be avoided. Do not use rags previously soiled by conventional inks.
 - Clean as if you are switching a deck from a dark colored ink to a pastel or white.
 - Thoroughly clean all pumps, hoses, and any other surface that may contact the ink. If possible, use new hosing and save after the run for future use with direct food contact inks. Disposable kit liners are also often used.
 - Allow all surfaces to dry prior to inking.

- Inking the Press:***
- Pour ink into the pan, or place ink into the pumping system, whichever is appropriate for your process.
 - Mix ink by either rotating anilox or pumping through system for 3-5 minutes.
 - Adjust to the optimum viscosity for the run, which will be dependent upon color, graphic, and drying requirements.
 - Use the solvent guidelines from the appropriate Colorcon Technical Data Sheet to adjust viscosity and drying rates.
 - If at anytime it is determined that a color adjustment is necessary, use only appropriate direct food contact inks or toners from Colorcon.

- During the Run:***
- Check viscosity approximately every thirty minutes (more frequently if press room conditions warrant) in order to maintain print quality.
 - For plate wash-up, use the same solvents used to thin the inks. Again, use only clean rags, or rags that have been only used with direct food contact inks.

- After the Run:***
- If pumping from kits or drums, remove the pump and seal the containers in order to prevent contamination.
 - Store under ambient conditions. Avoid freezing conditions, and keep away from sources of ignition.
 - Label the container as “press-return” ink.



For more information, contact your Colorcon representative or call 1-800-724-0624
You can also visit our website at <http://www.colorcon.com/notox>

©BPSI Holdings LLC, 2014

The information contained in this document is proprietary to Colorcon Inc. and may not be used or disseminated inappropriately.
All trademarks, except where noted, are property of BPSI Holdings, LLC.

The information contained herein, to the best of Colorcon Inc.'s knowledge, is true and accurate. Any recommendations or suggestions of Colorcon Inc. with regard to the products provided by Colorcon Inc. are made without warranty, either implied or expressed, because of the variations in methods, conditions and equipment which may be used in commercially processing the products, and no such warranties are made for the suitability of the products for any applications that you may have disclosed. Colorcon Inc. shall not be liable for loss of profit or for incidental, special or consequential loss or damages. The information contained in this document is not intended as legal advice, and should not be relied upon for that purpose. Any regulatory information provided is intended solely as initial general guidance. Each customer is responsible for determining the regulatory acceptability of the use of the product in their specific application.