

WHITE RAINBOW SPECIALTY INKS

IT17
(08/14)

Product Type: Dry Offset printing inks which are not visible when printed until activated by rubbing the image with a special crayon.

Printing Method: Sheetfed or Web Dry Offset processes must be used, utilizing raised image (i.e. Dycry, DuPont, USA) dry offset plates with rider bars.

Stocks: The following stocks have performed well with White Rainbow inks:

Sheetfed:	Web-fed:
Pathfinder Reply 73#	Weyerhaeuser Husky Smooth, 50# to
80# Pinehurst Smooth 80#	Pinehurst Smooth
Weyerhaeuser Husky Smooth 70#	Georgia Pacific Amherst Vellum
Various bleach-board stocks above .008, printed on the uncoated surface	

NOTE: The brighter the stock, the better the developed colors will appear due to the visual contrast. Avoid use of coated papers as images can smudge when rubbed by the crayon.

Artwork: As a standard lithographic black ink is generally used to print image outlines, care must be taken to assure that no White Rainbow ink prints directly over such an ink. Over time, toned or "muddy" images will occur as a result of the black contaminating the White Rainbow ink.

NOTE: Solid/block artwork is preferred to halftones, as halftones generally result in a loss of color vibrance.

Color Availability: Available in shades approximating process yellow, magenta, blue and black. Maximum color densities are reached 30 minutes after crayon activation.

General Printing Notes: Screen size for the plates should be 80 lines per inch or less for maximum color development.

Clean each deck prior to use to prevent color contamination. Clean as if the previous ink in the deck was black and now you wish to print an opaque white.

Print only one side of the paper with White Rainbow inks.

The printed pages, when cut and folded to create booklets, should never be face-to-face, only face-to-back.

Best results are achieved with the following ink sequence: Outline Black; White Rainbow Blue; White Rainbow Red; White Rainbow Yellow; White Rainbow Black.

Printed and cut forms coming off press can be pressure banded. Allow 48 hours after printing before finishing (binding & trimming).



For more information, contact your Colorcon representative or call 1-800-724-0624
You can also visit our website at [http:// www.colorcon.com/notox](http://www.colorcon.com/notox)

©BPSI Holdings LLC, 2014

The information contained in this document is proprietary to Colorcon Inc. and may not be used or disseminated inappropriately.
All trademarks, except where noted, are property of BPSI Holdings, LLC.

The information contained herein, to the best of Colorcon Inc.'s knowledge, is true and accurate. Any recommendations or suggestions of Colorcon Inc. with regard to the products provided by Colorcon Inc. are made without warranty, either implied or expressed, because of the variations in methods, conditions and equipment which may be used in commercially processing the products, and no such warranties are made for the suitability of the products for any applications that you may have disclosed. Colorcon Inc. shall not be liable for loss of profit or for incidental, special or consequential loss or damages. The information contained in this document is not intended as legal advice, and should not be relied upon for that purpose. Any regulatory information provided is intended solely as initial general guidance. Each customer is responsible for determining the regulatory acceptability of the use of the product in their specific application.