

No-Tox[®] **Products**

Technical Data

No-Tox® HEAT-RESISTANT POLYOLEFIN INKS

(FLEXOGRAPHIC/GRAVURE)

NT20 (12/14)

Product Type: Specially modified co-solvent polyamide.

Printing Method: Flexography or Gravure.

Suggested Uses: Designed to provide heat resistance when printed in the heat seal area of corona

treated polyolefin films. Resists softening or smudging at heat sealing

temperatures and pressures normally used to seal polyolefin films (low, medium and high density polyethylenes and polypropylenes). Can also be used on TYVEK (DuPont, USA) polyesters, nylon, Saran (Dow Chemical, USA)

(PVDC), some cellophanes and most paper stocks.

Plates and Rollers: Natural rubber and photopolymer plates and rollers.

Additives and Diluents*: Normally supplied at higher than "press-ready" viscosities to allow for diluent

and drying rate adjustment flexibility at press-side.

RecommendedFor FlexographyFor Rotogravure

Solvents: Normal: Normal:

75% Normal Propyl Alcohol 75% Normal Propyl Alcohol

25% Ethyl Acetate 25% Ethyl Acetate

Fast: Fast:

65% Normal Propyl Alcohol 50% Normal Propyl Alcohol

35% Ethyl Acetate 50% Ethyl Acetate

Slow:

70% Normal Propyl Alcohol 75% Normal Propyl Alcohol 30% Normal Propyl Acetate 25% Normal Propyl Acetate

Note: Due to the limited compatibility of the polymers used in this system, use only the

solvent blends recommended above. Avoid the use of other alcohols or

glycol-ethers.

Color Availability: 14 standard colors including process colors. Specific matches available upon

request

Shelf Life: Minimum one year in unopened containers.

Caution: Storage at low temperatures (45°F or lower) may cause gelling. Gelling can usually be

reversed by allowing the ink to come to room temperature and stirring with a high-shear

mixer.

FDA Acceptability*: All components used in No-Tox inks are sanctioned by the FDA and USDA

as acceptable for direct food contact.

*Note: FDA acceptability is based on the ink as supplied. Therefore, no materials should be added other than those indicated in this bulletin unless specifically recommended by Colorcon



For more information, contact your Colorcon representative or call 1-800-724-0624 You can also visit our website at http://www.colorcon.com/notox

©BPSI Holdings LLC, 2014
The information contained in this document is proprietary to Colorcon Inc. and may not be used or disseminated inappropriately.
All trademarks, except where noted, are property of BPSI Holdings, LLC.
The information contained herein, to the best of Colorcon Inc.'s knowledge, is true and accurate. Any recommendations or suggestions of Colorcon Inc. with regard to the products provided by Colorcon Inc. are made without warranty, either implied or expressed, because of the variations in methods, conditions and equipment which may be used in commercially processing the products, and no such warranties are made for the suitability of the products for any applications that you may have disclosed. Colorcon Inc. shall not be liable for loss of profit or for incidental, special or consequential loss or damages. The information contained in this document is not intended as legal advice, and should not be relied upon for that purpose. Any regulatory information provided is intended solely as initial general guidance. Each customer is responsible for determining the regulatory acceptability of the use of the product in their specific application.