

Reconstitution

Nutrapure™ certified organic coating is quick and easy to prepare. Simply add the Nutrapure powder to water and mix for 45 minutes with a propeller type stirrer (*It is normal for the Nutrapure powder to have a clumpy appearance*).

The coating suspension is typically recommended to be prepared at 10% solids concentration. Your Area Technical Manager can recommend the ideal solids for your specific Nutrapure formulation and your equipment.

MATERIALS

- Nutrapure powder
- Water, deionized or distilled preferred, ambient temperature (maximum 30 °C)

EQUIPMENT

- Variable-speed mixer capable of producing and maintaining a vortex.
- Propeller stirrer. For optimum mixing, utilize a propeller with a diameter equivalent to 1/3 - 1/2 of the diameter of the mixing vessel. (Figure 1)
- Mixing vessel large enough to contain a liquid volume 15% to 25% greater than the total suspension being prepared. The liquid height and vessel diameter should be equal.


MIXING PROCEDURE

1. Weigh necessary quantity of Nutrapure powder.
2. Weigh necessary quantity of water into the mixing vessel.
3. With the propeller in the center and as close to the bottom of the vessel as possible, stir the water to form a vortex without drawing air into the liquid.
4. Steadily add the Nutrapure powder to the vortex. It is normal for the powder to have a clumpy appearance. Large clumps will easily disperse over the recommended mixing time.
5. After all the Nutrapure powder has been added, reduce the mixer speed to nearly eliminate the vortex. Mix for 45 minutes.

SUSPENSION HANDLING

The prepared Nutrapure dispersion can be pumped directly from the preparation vessel if desired.

Figure 1



SUSPENSION HOLD TIME / MICROBIAL CONSIDERATIONS

Nutrapure is comprised of minimally processed, plant based food materials and, therefore, is susceptible to microbial growth once the dispersion is prepared and exposed to different environmental conditions (air and water). The water used can have varying levels of microbial quality (even if it complies with cGMP's), depending on the system and source supply.

It is recommended that Nutrapure dispersions, as prepared using this procedure, be used for coating immediately after preparation and not held for extended periods.

However, if desired, it is possible to extend the hold time of the Nutrapure dispersion by adding a small quantity of hydrogen peroxide* (30% H₂O₂) at 0.04% w/w of total suspension quantity to the water prior to the addition of Nutrapure. Using this method, microbial growth in the dispersion can be controlled at very low levels for hold times up to 48 hours.

**Hydrogen peroxide is allowed for Organic use per: USDA Subpart G—Administrative The National List of Allowed and Prohibited Substances; § 205.605 Non-agricultural (nonorganic) substances allowed as ingredients in or on processed products labeled as “organic” or “made with organic (specified ingredients or food group(s))”; (b) Synthetics allowed.*

The information contained herein, to the best of Colorcon, Inc.'s knowledge is true and accurate. Any recommendations or suggestions of Colorcon, Inc. with regard to the products provided by Colorcon, Inc. are made without warranty, either implied or expressed, because of the variations in methods, conditions and equipment which may be used in commercially processing the products, and no such warranties are made for the suitability of the products for any applications that you may have disclosed. Colorcon, Inc. shall not be liable for loss of profit or for incidental, special or consequential loss or damages.

The information contained herein, to the best of Colorcon, Inc.'s knowledge is true and accurate. Any recommendations or suggestions of Colorcon, Inc. with regard to the products provided by Colorcon, Inc. are made without warranty, either implied or expressed, because of the variations in methods, conditions and equipment which may be used in commercially processing the products, and no such warranties are made for the suitability of the products for any applications that you may have disclosed. Colorcon, Inc. shall not be liable for loss of profit or for incidental, special or consequential loss or damages.

Colorcon, Inc. makes no warranty, either expressed or implied, that the use of the products provided by Colorcon, Inc., will not infringe any trademark, trade name, copyright, patent or other rights held by any third person or entity when used in the customer's application.

For more information, contact your Colorcon representative or call:

North America +1-215-699-7733	Europe/Middle East/Africa +44 (0)-1322-293000	
Latin America +54-11-5556-7700	India +91-832-6727373	China +86-21-61982300

You can also visit our website at www.colorcon.com



© BPSI Holdings, LLC 2018. The information contained in this document is proprietary to Colorcon and may not be used or disseminated inappropriately.

All trademarks, except where noted, are property of BPSI Holdings, LLC.